

SPECIFICATION

ITEM	INFRARED TOUCH SCREEN
MODEL	NIB
PART NUMBER	NIB-220B
BUYER	
DATE	MAR. 10, 2008

APPROVED BY

NEXIO CORPORATION	
DRAWN BY	H.J Kim
CHECKED BY	E.R Bae
APPROVED BY	K.S Kim



Nexio Co., Ltd.

5F, Seong-Woong B/D, 898-3, Jakjun-dong,
Gyeyang-gu, Incheon, Korea

Tel : +82 32 556 9545~7

Fax : +82 32 556 9544

CONTENTS

1. Revision History	-----	3
2. Mechanical	-----	4
3. Touch Characteristics	-----	4
4. Electrical	-----	4
5. Environment	-----	4,5
6. Controller	-----	5
7. Touch Panel Drawing	-----	Appendix1
8. Driver Manual	-----	Appendix2

1. Revision History

Date	Rev. No	Page	Summary
MAR.10,2008	S-080310-001		Approval specification of NIB-220B model was issued first.

2. Mechanical

Housing	Black powder coated Metal
Touch Size (Out line)	542(w) x 364(h) x 11.5(d)mm
Useful Screen Area	470.8(h) x 294.3(v)
Weight	3.5Kg
Drawing	Please refer to Appendix 1

3. Touch Characteristics

Input Method	Finger or gloved hand activation
Touch Activation Force	No minimum touch activation force
Position Accuracy	Typical centroid accuracy 2mm
Resolution	5,696 x 3,584
Response Time	Touch : 12ms
	Drawing : 19ms
Glass	Transmission : 92% Up to 100%
	Thickness : 5 mm with anti-vandal
Optics Number	89(h) x 56(v)
Optics cell pitch	5.35mm
Available Object Sizes for Touch	Touch : Ø7mm
	Stylus : Ø8mm
Touch Intensity	Over 60,000,000 single point touch

4. Electrical

Operating Voltage	DC 4.6V ~ DC 5V
Power	0.6W(Current) 120mA at DC 5V
Connector between touch panel and controller	22pin FPC cable
ESD	TBD

5. Environment

Temperature	Operating -20°C to 85°C
	Storage -40°C to 85°C
Humidity	Operating 20% to 85%
	Storage 0~95%
Relative Humidity	Operating 40°C at 90% RH, Noncondensing
Light Test	Incandescent lamp (220V,60W) , Operating distance 400mm over
Altitude Operating	3,000m
Interface	RS232(C) or USB 1.1
Detection Method	Infrared rays
Seal Ability	IP54

Warranty	Touch screen : 5 -years limited warranty
	Controller : 5 -years limited warranty
Working place	Not working under sunlight, for Indoor used application.

6. Controller

6.1 Interface Connector : YEON-HO 10008HR-22L (22pin FPC Cable)

6.2 Input Connector CN2 : Power Connector(Molex.5267-03, YEON-HO YMW023-03R)

Pin NO.	Symbol	Description
1	GND	GND
2	GND	GND
3	Vin	Input Voltage : 5V

6.3 Interface Connector CN3 : Serial Connector(Molex.53015-0510, YEON-HO 20017WR-05)

Pin NO.	Symbol	Description
1	RX	Received Data
2	TX	Transmit Data
3	GND	GND
4	NC	No connection
5	NC	No connection

6.4 Interface Connector CN4 : USB B type Female.

6.5 Drawing : Please refer to Appendix1

7. Touch Panel Drawing : Please refer to Appendix1.

8. Driver Manual : Please refer to Appendix2.

Note : The specification is subject to change without prior notice.